




CS-205A Ceiling Speaker (Quick-Mounting Type)



FEATURES:

- Dished grille design for acoustic integrity.
- 6.5" twin cone speaker is suitable for music & speech reproduction.
- 6W transformer with multi tapping applications.
- Integrated design used in various places.
- Wide dynamic range can keep in large volume output without distortion.
- Space saving design.
- Easy installation secured by two integral spring-loaded quick-mounted locking clamps.
- Optional steel fire dome (FD-21).

Installation method



Model No.	CS-205
Rated Input	6W
Max Input	9W
Impedance	1.7kΩ, 3.3kΩ,
Power Taps	100V: 6W, 3W; 70V: 3 W, 1.5W
SPL(1W /1m)	90dB
MAX SPL(Rated /1m)	96dB
Frequency Response(-10dB)	100Hz~18kHz
Dispersion (4kHz / 1kHz)	55° / 160°
Power Selecting Way	Three core cables: Blue 1.7kΩ, Red 3.3kΩ, Black: COM
Material	Panel &Grille: Steel
Color	White
Temperature / Humidity	-20°C ~55°C; <95%
Speaker Component	6.5" Twin Cone Speaker
Dimensions	Ø200 x 65H mm
Mounting Hole	Ø 170 x 75H mm, Max Ceiling Thickness:25mm
Weight	0.7kg
Mounting	Two Integral Spring-loaded Quick-Mounted Locking Clamps
Shipping Weight	15kg, 20pcs
Shipping Dimensions	0.0669CBM, 42 x 37 x43 cm, 20pcs