

GS-5CT/6CT/8CT GS series high-end ceiling speaker



FEATURES:

- Outstanding ceiling speakers from brand of Thinuna.
- Stunning exceptional quality.
- Designed for professional audio and commercial audio field.
- Innovative magnetic mask for easy installation.
- Treble can adjust the angle of rotation can be more precise control of the sound field.
- Imported superior tweeter: 20 core (GS-5CT), 25 core (GS-6CT, GS-8CT) voice coil / imported transparent silk sound film.
- Good imported polypropylene woofer.
- Treble transparent, bright, soft, not annoying.
- Surging bass strong, thick solid.
- Built-in high quality divider in two-frequency divider system.
- Front guide holes for strengthened bass.
- All models are equipped with 100/70V and 8Ω selector switches.
- Built-in 100V / 70V transformer for business matching audio system and provides multi-gear power selection
- Concave punch grille enhance the sound reproduction.
- Rotary mounting ears makes installation easy and simple.
- Safety rope connection port, with steel wire rope protection.

GS Series ceiling speakers are outstanding ceiling speakers of Thinuna. The entire series of products are designed with the aim of pursuing perfect sound quality, with features as high-fidelity, high-power, high sound pressure level etc...

Each speaker has a stunning performance. Accurate design of frequency divider and inverted hole can make the level of bass and bass more distinct and more in line with various installation needs

choosing this distinguished ceiling speaker series means choosing quality, This high-quality music and voice reproduction, definitely used to meet many demanding workplace. such as: brand stores, a conference center, banquet hall, high-end Western restaurants, railway stations, airports and any pursuit of quality of place.

All models are equipped with 100/70V and 8Ω selector switches, which provide multi-gear power selection for constant-voltage input connections, suitable for a wide range of public broadcasting and commercial audio systems.



GS-5CT/6CT/8CT GS series high-end ceiling speaker

Specification:

Type	GS- 5CT	GS- 6CT	GS- 8CT
Rate Power	20W@100V; 30W@8Ω	40W@100V; 60W@8Ω	60W@100V; 90W@8Ω
Max power	30W@100V; 45W@8Ω	60W@100V; 90W@8Ω	90W@100V; 120W@8Ω
Impedance Constant Voltage	250Ω, 500Ω, 1kΩ, 2kΩ, 4kΩ	125Ω, 250Ω, 500Ω, 1kΩ, 2kΩ	83Ω, 167Ω, 333Ω, 666Ω, 1.3kΩ
Constant power	100V:NC, 20W,10W,5W,2.5W. 70V:20W,10W,5W,2.5W,1.25W	100V:NC, 40W,20W,10W,5W. 70V:40W,20W,10W,5W,2.5W	100V:NC, 60W,30W,15W,7.5W. 70V:60W,30W,15W,7.5W,3.75W
SPL(1W/1m)	87dB	89dB	90dB
Max SPL (Rated / 1m)	102dB@100V; 103dB@8Ω	107dB@100V; 108dB@8Ω	109dB@100V ; 110dB@8Ω
Frequenc response(-10dB)	80Hz~23kHz	65Hz~23kHz	53Hz~23kHz
Spread angle (4kHz / 1kHz)	70° / 140°	65° / 140°	50° / 100°
Power selection	Rotary selector switch		
Material	Panel & Rear cowl: ABS; Protector: iron		
Colour	Front face shield: white; Rear canister:black		
Operating Temp	-20°C ~55°C; <95%		
Speakers Unit	4'' Bass + 1'' Treble	5.25'' Bass + 1'' Treble	6'' Bass + 1'' Treble
Size	Ø205 x180H mm	Ø238 x200H mm	Ø265 x205H mm
Hole size	Ø175mm	Ø205mm	Ø230mm
Weight	2.6kg	3.16kg	4.2kg
Installation	4 Claw rotatably mounted ear		
Gross weight	24.5kg, 8pcs	16.3kg, 4pcs	19.7kg, 4pcs
Packing Size	0.0932CBM 45X45X46cm, 8pcs	0.0431CBM 55X28X28cm, 4pcs	0.1008CBM 60X60X28cm, 4pcs