



# HW-10B/20B Metallic Projection Speaker






## FEATURES:

- Dust-proof and waterproof grades in accordance with IEC529 IP55 standard.
- Designed to control sound directivity.
- Another ideal choice for wide range frequency projection speaker.
- Ideal for music and speech applications.
- Stable long-life Aluminum alloy cover with strong anticorrosion, can avoid all kinds of bad weather.
- Built-in 100V/70V matching transformer and provide three-gear power selection.
- Amazing SPL for powerful and clear sound quality.
- 5.25" and 6.5" waterproof unit.
- Including U type bracket for fast and easy installation

## Installation method



**HW-10B**



**HW-20B**

| Model No.                 | HW-10B   | HW-20B                                       |
|---------------------------|--|--|
| Rated Input               | 10W  | 20W  |
| Max Input                 | 20W  | 40W  |
| Impedance                 | 1KΩ, 2KΩ, 4KΩ  | 500Ω, 1KΩ, 2KΩ                               |
| Power Taps                | 100V: 10 W, 5 W, 2.5W<br>70V: 5 W, 2.5 W, 1.25W  | 100V: 20 W, 10 W, 5W<br>70V: 10 W, 5 W, 2.5W |
| SPL (1W /1m)              | 91dB   | 92dB   |
| MAX SPL (Rated /1m)       | 101dB  | 105dB  |
| Frequency Response(-10dB) | 130Hz~15kHz  | 110Hz~15kHz                                  |
| Dispersion (4kHz / 1kHz)  | Uni-direction: 230° / 65°  |  |
| Power Selecting Way       | Four Core Cable;Red: Rated impedance; Yellow: Twice Rated Impedance; Green: Quadrupling Rated Impedance; Blue: COM |  |
| Material                  | Case: Aluminum alloy;Grille: Steel   |  |
| Color                     | Brilliant White  |  |
| Temperature / Humidity    | -30°C ~60°C; <95%  |  |
| Water Protection          | IEC529 IP55  |  |
| Speaker Component         | 5.25" twin cone speaker  | 6.5" twin cone speaker                       |
| Dimensions                | Ø138 x205Lmm   | Ø170 x252Lmm                                 |
| Weight                    | 2.2kg  | 2.8kg  |
| Mounting                  | U Type Mounting Bracket  |  |
| Shipping Weight           | 20kg, 8pcs   | 20kg, 6pcs                                   |
| Shipping Dimensions       | 0.0816CBM, 74 x 38 x29 cm, 8pcs  | 0.1059CBM, 65 x 44 x37 cm, 6pcs              |