

IP-9614AO III M/IP-9614AO III S Network active speaker



FEATURES:

Any place with an Ethernet port can be accessed. It can play network audio and can accept the access and control of servers and other IP network devices.

Network fault self-diagnosis, with 24V POE power supply network port and TCP/IP network port.

Built-in 2*15W stereo digital power amplifier, power amplifier heat low, safe and reliable, suitable for long time work. Simple connection and convenient use.

Speaker unit 5" Woofer + 1" tweeter, clear and pleasant sound quality.

ABS engineering plastic, metal mesh mask. Equipped with special mounting bracket, can be installed vertically or horizontally.

Suitable for use in classroom, meeting room, restaurant, shopping mall and other places.

Optional: 2.4G wireless microphone (built-in version).

Thinuna IP-9614AO III S Network Slave Speaker

Speaker unit 5" Woofer + 1" tweeter, clear and pleasant sound quality.

ABS engineering plastic, metal mesh mask. Equipped with special mounting bracket, can be installed vertically or horizontally.

Suitable for use in classroom, meeting room, restaurant, shopping mall and other places.



IP-9614AO III M/IP-9614AO III S Network active speaker

Model	IP-9614AO III M
Network interface	External standard RJ45, 10M/100M network port, network port comes with upgrade function
Support protocols	TCP, UDP, IGMP, ICMP, ARP
Audio format	PCM (Uncompressed format), ADPCM, MP3
Restart recovery time of power and network disconnection	<1s
Network delay	File playback: less than 50ms, real-time speech: less than 150ms
Transmission rate	10/100Mbps
Audio mode	Network data packet
Amplifier frequency response	20Hz ~ 20KHz
Harmonic distortion	≤0.3%
SNR	> 90dB
Rated output	Built-in 2*15W digital power amplifier, built-in 15W full-range speaker, one power amplifier output, can be connected with external fixed resistance speaker (8~16 ohms, power within 15W)
Operating temperature	-20°C ~ +60°C
Operating humidity	10%~90%
Power consumption	≤40 W
Speaker sensitivity	93dB±3dB
Speaker frequency range (-10dB)	100Hz -16kHz
Input power	External power supply DC24V, support 24V POE power supply
Dimensions	270(W)×165(H)×85(D)mm
Cabinet color	White/black

Model	IP-9614AO III S
Rated power	15W
Speaker impedance	8Ω
Operating temperature	-20°C~+60°C
Operating humidity	10%~90%
Speaker sensitivity	93dB±3dB
Speaker frequency range (-10dB)	100Hz -16kHz
Dimensions	270(W)×165(H)×85(D)mm
Cabinet color	White/black
Weight	1.3Kg