

# IP-9614AO III Network Audio Terminal



### FEATURES:

1. Any place with an Ethernet port can be accessed. It can play network audio and can accept the access and control of servers and other IP network devices.
2. Network fault self-diagnosis, network and service status display.
3. Equipped with 24V POE power supply network port and TCP/IP network port.
4. It has 1- channel local stereo input and 1-channel local microphone input function (mixing).
5. Built-in 2 \* 15W stereo digital power amplifier with low heat output. Safe and reliable, suitable for long working hours.
6. Optional: 2.4G wireless microphone and Bluetooth audio input function (mixing).

Model	IP-9614AO III
Network interface	Standard RJ45, 10M/100M dual network port, network port comes with upgrade function
Support protocols	TCP, UDP, IGMP, ICMP, ARP
Audio format	PCM (uncompressed format), ADPCM, MP3
Restart recovery time of power and network disconnection	< 1s
Network delay	File playback is less than 50ms, real-time speech is less than 150ms, with automatic cache function
less than 50ms, real-time speech	less than 150ms
Transmission rate	10/100Mbps
Audio mode	network packet
Frequency response	20Hz ~ 16KHz
THD	≤0.3%
SNR	> 75dB
Local audio input interface	3.5mm stereo input, 3.5mm microphone input, Bluetooth input, 2.4G wireless microphone input
Line input level	1.4V RCA
Rated output	2 * 15W fixed resistance output
Operating temperature	-20°C ~ +60°C
Working humidity	10%~ 90%
Power consumption	≤40W
Input power	external power supply DC24V, supporting 24V POE power supply
Dimensions	103(W)x45(H)x63(D) mm