

IP-9633RM III Network Microphone Workstation



FEATURES:

1. Any place with an Ethernet port can be accessed. It can play network audio and can accept the access and control of servers and other IP network devices.
2. Network fault self-diagnosis, network and service status display.
3. New desktop appearance design, 7-inch TFT true color screen, graphical interface display, full-capacitive touch screen control, convenient and fast, high-end and beautiful.
4. The core equipment of network intercom, which can directly broadcast to the partition and various types of playback equipment.
5. Can directly paging and two-way talk with the intercom equipment on the network.
6. External gooseneck microphone, built-in speaker (5W).
7. Support multi-party calls during intercom.
8. Paging and intercom PTT (Push To Talk) control function.
9. Line input and output port, which can transmit local audio signals to the network.

Model No.	IP-9633RM III
Network interface	Standard RJ45, 10M/100M network port, network port comes with upgrade function
Support protocols	TCP,UDP,IGMP,ICMP,ARP
Audio format	PCM(Uncompressed format) , ADPCM,MP3
Input	- 10 dB,RCA, stereo
Output	0dB,RCA, stereo
Frequency response	Aux:20Hz~20kHz;Mic: 50Hz~ 15kHz
Touch screen	7 inches; resolution: 1024 × 600; color: 64K color, 16RGB, true color
Text	GUI, picture, animation display and touch control
EQ	Treble : ±12dB at 10kHz;bass : ±12dB at 100Hz
Phantom power	DC24V
UART	RS-232
THD	< 0.01% at 100Hz~10kHz
SNR	> 90dB
Power supply	External power supply DC24V,1A
Power consumption	< 10W
Weight	1.7kg
Dimension	218 (W) ×80 (H) ×187 (D) mm ; Gooseneck microphone length : 390mm